

Substitute fuses for the NIHON AIRPAX brand

NIHON AIRPAX brand fuses						HINODE equivalent fuses					
Model	Rated voltage	Rated current rms(A)	Installation dimensions		Terminal shape	Model	Rated voltage	Rated current	Installation dimensions		Terminal shape
			Pitch	Diam.					Pitch	Diam.	
QAD25-50	AC250/125	50	58	φ 8.5	Center blade	250GAR50	250	50	59	φ 10	Center blade
QAD25-75		70				75					
QAD25-100		100				100					
QAD25-150		150				150					
QAD25-200		200				200					
QAD25-250		250				250					
QAC25-30	AC250/125	30	60	φ 9.5	Center blade	250GAR50	250	50	59	φ 10	Center blade
QAC25-50		50				50					
QAC25-75		75				75					
QAC25-100		100				100					
QAC25-150		150				150					
QAC25-200		200				200					
QAC25-250		250				250					
QAC25-300		300				300					
QAC25-400		400				400					
QAC25-500		500				500					
QAC25-600	600	600									
QAC50-30	AC500/600	30	89	φ 9.5	Center blade	500GAR30	500	30	91	φ 10	Center blade
QAC50-50		50				50					
QAC50-75		75				75					
QAC50-100		100				100					
QAC50-150		150				150					
QAC50-200		200	200								
QAC50-250		250	250								
QAC50-300		300	300								
QAC50-400		400	400								
QAC50-500		500	500								
QAC50-600	600	600									
QAB12-50	AC125	50	57	9 × 14	Center blade	250GAR50	250	50	59	φ 10	Center blade
QAB12-75		75				75					
QAB12-100		100				100					
QAB12-150		150				150					
QAB12-200		200				200					
QAB12-250		250				250					
QAB12-300	300	300									
HQA12-350	AC125	350	74	9 × 17	Center blade	250GAR400	250	400	71	φ 11	Center blade
HQA12-400		400				400					
HQA12-500		500				500					
HQA12-600		600				600					
HQA12-800		800				800					
HQA12-1000		1000				1000					
QAB25-50	AC250	50	57	9 × 14	Center blade	250GAR50	250	50	59	φ 10	Center blade
QAB25-75		75				75					
QAB25-100		100				100					
QAB25-150		150				150					
QAB25-200		200				200					
QAB25-300		300				300					
QA25-15	AC250	15	Cylinder length = 50	Terminal diam. = φ 15 Max. diameter = φ 19	Cylinder	800CF-15UL	660	15	Cylinder length = 51	Terminal diam. = φ 14.6 Max. diameter = φ 14.6	Cylinder
QA25-20		20				20					
QA25-25		25				25					
QA25-30		30				30					
QA40-100	AC400	100	95	9 × 17	Center blade	500GAR100	500	100	91	φ 10	Center blade
QA40-150		150				150					
QA40-200		200				200					
QA40-250		250				250					
QA60-150	AC600	150	102	9 × 17	Center blade	F70P-150	700	150	92	8.5 × 11	Center blade

- * The substitute products that equal or resemble the terminal shapes, installation dimensions and rated voltage/current are listed. Please check the product specifications in the HINODE and NIHON AIRPAX catalogues.
- * If the fuse replacement is made by someone other than the circuit developer, Hinode will not be responsible for the operation. Even if it is made by the circuit developer, please make sure that the replacement fuse you select is suitable and matches current requirements. Safety and security in design and use are the user's responsibility.
- * NIHON AIRPAX is not connected in any way with the data displayed here. Please send all inquiries to HINODE..

Issued on Jan. 26, 2009
 Revised on Nov. 24, 2009
 Issued by HINODE ELECTRIC CO., LTD.
 TEL.: 03-3860-8661 FAX: 03-3860-8660
 E-mail: uketsuke@hinodedenki.co.jp